


İğne Tip İzoleli Kablo Uçları




Malzeme : Bakır (E-Cu), Kalay Kaplı
İzolasyon : Naylon
Çalışma Sıcaklığı : Maksimum 105 °C 600 Volt




	Kablo Kesiti (mm ²)	Ebatlar (mm)									Koli Miktan (Ad)	Ambalaj Ağırlığı (~gr)
		W	F	L	E	D	d1	T				
	IK-101I	0,50 - 1,50	1,9	10,0	19,8	10,0	4,0	1,7	0,75	200	12.000	174
	IK-102I	1,50 - 2,50	1,9	12,0	21,8	10,0	4,5	2,3	0,80	200	12.000	210
	IK-106I	4,00 - 6,00	2,8	14,0	27,0	13,0	6,4	3,4	1,00	100	6.000	228

Bıçak Tip İzoleli Kablo Uçları



Malzeme : Bakır (E-Cu), Kalay Kaplı
İzolasyon : PVC
Çalışma Sıcaklığı : Maksimum 75 °C 600 Volt




	Kablo Kesiti (mm ²)	Ebatlar (mm)									Koli Miktarı (Ad)	Ambalaj Ağırlığı (~gr)
		W	F	L	E	D	d1	T				
	IK-101/14	0,50 - 1,50	3,0	14,0	23,8	10,0	4,0	1,7	0,75	200	12.000	180
	IK-102/18	1,50 - 2,50	2,2	18,0	27,8	10,0	4,5	2,3	0,80	200	12.000	206

Ek Mufları İzoleli Kablo Uçları



Malzeme : Bakır (E-Cu), Kalay Kaplı
İzolasyon : PVC
Çalışma Sıcaklığı : Maksimum 75 °C 600 Volt




Ürün Kodu	Kablo Kesiti (mm ²)	Ebatlar (mm)			Koli Miktarı (Ad)	Ambalaj Ağırlığı (~gr)
		L	D	d1		
BY-251	0,50 - 1,50	24,6	4,0	1,7	200	275
BY-252	1,50 - 2,50	24,6	4,5	2,3	200	322
BY-256	4,00 - 6,00	26,5	6,3	3,4	100	285

DIN 46230 Tip İzolesiz Kablo Ucu (Kaynaklı)



Malzeme : Bakır (E-Cu), Kalay Kaplı



	Kablo Kesiti (mm ²)	Ebatlar (mm)									Ambalaj Ağırlığı (~gr)
		W	F	L	E	D	d1	T			
IK-110/12I	10	4,3	14,0	22,0	8,0	6,9	4,5	1,1	500	24,5	
IK-116/13I	16	5,5	16,0	26,0	10,0	8,4	5,8	1,2	250	29,7	
IK-125/15I	25	6,8	20,0	33,5	13,5	9,5	7,0	1,2	100	40,5	
IK-135/20I	35	8,0	24,5	40,5	16,0	11,8	8,4	1,5	50	40,0	
IK-150/20I	50	9,5	26,0	45,0	19,0	13,6	9,6	1,8	50	47,0	
IK-170/25I	70	11,0	31,0	55,0	24,0	15,8	11,4	2,0	25	59,0	
IK-195/25I	95	12,5	31,0	55,0	24,0	18,9	13,5	2,5	20	44,5	