


İzoleli Çift Girişli Kablo Yüksükleri DIN 46228



Standart : DIN 46228
Malzeme : Bakır (E-Cu), Kalay Kaplı
İzolasyon : Naylon
Çalışma Sıcaklığı : Maksimum 105 °C 600 Volt




Kablo Kesiti (mm ²)		Renk	Ebatlar (mm)							Koli Miktarı (Ad)	Ambalaj Ağırlığı (~gr)
			F	L	W	B	D	C			
2 x 0,50	UY-23005	 Beyaz	8,0	14,5	5,0	6,5	1,8	1,5	500	30.000	107
2 x 0,75	UY-23007	 Mavi	8,0	14,7	5,5	6,7	2,1	1,8	500	30.000	121
2 x 1,00	UY-23010	 Kırmızı	8,0	15,1	5,5	7,1	2,4	2,1	500	30.000	137
2 x 1,50	UY-23015	 Siyah	8,0	15,5	6,4	7,5	2,6	2,3	500	25.000	164
2 x 2,50	UY-23025	 Gri	10,0	18,5	8,0	8,5	3,3	2,9	250	12.500	137
2 x 4,00	UY-23040	 Turuncu	12,0	23,1	8,8	11,1	4,2	3,8	100	6.000	98
2 x 6,00	UY-23060	 Yeşil	14,0	26,1	9,5	12,1	5,3	4,9	100	5.000	149
2 x 10,00	UY-23100	 Kahve	14,0	26,6	12,6	12,6	6,9	6,5	50	3.000	108
2 x 16,00	UY-23160	 Bej	14,0	31,3	19,0	17,3	8,7	8,3	50	2.500	56

Şafak Serisi İzolesiz Kablo Yüksükleri DIN 46228



Standart : DIN 46228
Malzeme : Bakır (E-Cu), Kalay Kaplı



Kablo Kesiti (mm ²)	Ürün Kodu	Ebatlar (mm)				Koli Miktarı (Ad)	Ambalaj Ağırlığı (~gr)
		L	D	C	W		
0,50	KY-0,50/6	6,0	1,3	1,0	1,7	1.000	54,0
0,50	KY-0,50	10,0	1,3	1,0	1,7	1.000	76,0
0,75	KY-0,75	10,0	1,5	1,2	1,9	1.000	85,0
1,00	KY-1,00	10,0	1,7	1,4	2,2	1.000	92,0
1,50	KY-1,50/7	7,0	2,0	1,7	2,5	1.000	83,0
1,50	KY-1,50	10,0	2,0	1,7	2,5	1.000	104,0
2,50	KY-2,50/8	8,0	2,6	2,3	3,3	1.000	112,0
2,50	KY-2,50	12,0	2,6	2,3	3,3	1.000	180,0
4,00	KY-4,00	12,0	3,2	2,8	3,9	500	155,0
6,00	KY-6,00	12,0	3,9	3,5	4,7	500	175
10,00	KY-10/12	12,0	4,9	4,5	5,8	250	131
10,00	KY-10	15,0	4,9	4,5	5,8	250	156
16,00	KY-16/12	12,0	6,2	5,8	7,2	100	67
16,00	KY-16	15,0	6,2	5,8	7,2	100	78
25,00	KY-25	15,0	7,9	7,5	9,1	100	114
35,00	KY-35	15,0	8,7	8,3	10,2	100	121
50,00	KY-50	22,0	10,9	10,3	12,7	100	217
70,00	KY-70	25,0	14,3	13,5	15,8	50	398
95,00	KY-95	30,0	15,6	14,8	17,3	50	511
120,00	KY-120	34,0	17,7	16,7	20,2	25	846
150,00	KY-150	38,0	20,6	19,6	23,0	25	1.026